

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting with a CRI of 90 for a better color accuracy.


Aluminium fixture, white or black powder coated, with several possible reflectors (16°, 26°, 42°)
Available in two different versions: the high efficiency (700mA) or the high output (1750mA) version.

Standard equipped with torsion springs.

**TECHNICAL DATA**

Application	ceiling - recessed
Dimensions	cut out: Ø150mm h170mm
IP rating	IP20
Power	700mA / 1750mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	23,3W	700mA	2940 lm	126 lm/W	90	A+
	65,8W	1750mA	6350 lm	97 lm/W	90	A+
3000K	23,3W	700mA	3260 lm	140 lm/W	90	A++
	65,8W	1750mA	7000 lm	106 lm/W	90	A+
3500K	23,3W	700mA	3280 lm	141 lm/W	90	A++
	65,8W	1750mA	7050 lm	107 lm/W	90	A+
4000K	23,3W	700mA	3480 lm	149 lm/W	90	A++
	65,8W	1750mA	7430 lm	113 lm/W	90	A+

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector) option only for 2700K or 3000K

2700K

HE 700mA

16°	ZUMI0110692702082	Cannon Select SLE G5 HE 23,3W 700mA 2940 lm 2700K CRI90 16° glass excl. conv.
26°	ZUMI0110692703082	Cannon Select SLE G5 HE 23,3W 700mA 2940 lm 2700K CRI90 26° glass excl. conv.
42°	ZUMI0110692704082	Cannon Select SLE G5 HE 23,3W 700mA 2940 lm 2700K CRI90 42° glass excl. conv.

HO 1750mA

16°	ZUMI0110692702112	Cannon Select SLE G5 HO 65,8W 1750mA 6350 lm 2700K CRI90 16° glass excl. conv.
26°	ZUMI0110692703112	Cannon Select SLE G5 HO 65,8W 1750mA 6350 lm 2700K CRI90 26° glass excl. conv.
42°	ZUMI0110692704112	Cannon Select SLE G5 HO 65,8W 1750mA 6350 lm 2700K CRI90 42° glass excl. conv.

3000K

HE 700mA

16°	ZUMI0100793002082	Cannon Select SLE G5 HE 23,3W 700mA 3260 lm 3000K CRI90 16° glass excl. conv.
26°	ZUMI0100793003082	Cannon Select SLE G5 HE 23,3W 700mA 3260 lm 3000K CRI90 26° glass excl. conv.
42°	ZUMI0100793004082	Cannon Select SLE G5 HE 23,3W 700mA 3260 lm 3000K CRI90 42° glass excl. conv.

HO 1750mA

16°	ZUMI0100793002112	Cannon Select SLE G5 HO 65,8W 1750mA 7000 lm 3000K CRI90 16° glass excl. conv.
26°	ZUMI0100793003112	Cannon Select SLE G5 HO 65,8W 1750mA 7000 lm 3000K CRI90 26° glass excl. conv.
42°	ZUMI0100793004112	Cannon Select SLE G5 HO 65,8W 1750mA 7000 lm 3000K CRI90 42° glass excl. conv.

3500K*HE 700mA*

16°	ZUMI0110793502082	Cannon Select SLE G5 HE 23,3W 700mA 3280 lm 3500K CRI90 16° glass excl. conv.
26°	ZUMI0110793503082	Cannon Select SLE G5 HE 23,3W 700mA 3280 lm 3500K CRI90 26° glass excl. conv.
42°	ZUMI0110793504082	Cannon Select SLE G5 HE 23,3W 700mA 3280 lm 3500K CRI90 42° glass excl. conv.

HO 1750mA

16°	ZUMI0110793502112	Cannon Select SLE G5 HO 65,8W 1750mA 7050 lm 3500K CRI90 16° glass excl. conv.
26°	ZUMI0110793503112	Cannon Select SLE G5 HO 65,8W 1750mA 7050 lm 3500K CRI90 26° glass excl. conv.
42°	ZUMI0110793504112	Cannon Select SLE G5 HO 65,8W 1750mA 7050 lm 3500K CRI90 42° glass excl. conv.

4000K*HE 700mA*

16°	ZUMI0100894002082	Cannon Select SLE G5 HE 23,3W 700mA 3480 lm 4000K CRI90 16° glass excl. conv.
26°	ZUMI0100894003082	Cannon Select SLE G5 HE 23,3W 700mA 3480 lm 4000K CRI90 26° glass excl. conv.
42°	ZUMI0100894004082	Cannon Select SLE G5 HE 23,3W 700mA 3480 lm 4000K CRI90 42° glass excl. conv.

HO 1750mA

16°	ZUMI0100894002112	Cannon Select SLE G5 HO 65,8W 1750mA 7430 lm 4000K CRI90 16° glass excl. conv.
26°	ZUMI0100894003112	Cannon Select SLE G5 HO 65,8W 1750mA 7430 lm 4000K CRI90 26° glass excl. conv.
42°	ZUMI0100894004112	Cannon Select SLE G5 HO 65,8W 1750mA 7430 lm 4000K CRI90 42° glass excl. conv.

> CONVERTER*HE 700mA***dimmable**

ZUMI28000125278 LCAI 35W 700mA ECO SR + I SELECT PLUG (DALI, DSI, switchDIM)

non dimmable

TRID24166314 LCI 30W 700mA IP20

*HO 1750mA***dimmable**

ZUMI28000256274 LCAI 100W 1750mA ECO SR + I SELECT PLUG + LCF 12V Fandr. (DALI, DSI, switchDIM)

non dimmable

ZUMI28000204274 LCI 100W 1750mA TOP SR + I SELECT PLUG + LCF 12V Fandriver

> OPTIONS**PC-cover**

ZUMI010000000500 PC-cover for food environment Ø 111

Flat Springs

ZUMIFS Flat Springs

Emergency kit

On request