

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting. The art version is with its CRI 98 the perfect solution to enlighten art and musea.


Aluminium fixture, white or black powder coated, with several possible reflectors (16°, 26°, 42°)
Available in two different versions: the high efficiency (700mA) or the high output (1750mA) version.

Standard equipped with torsion springs.

**TECHNICAL DATA**

| | |
|-----------------------|------------------------|
| Application | ceiling - recessed |
| Dimensions | cut out: Ø150mm h170mm |
| IP rating | IP20 |
| Power | 700mA / 1750mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 2 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 2700K | 23,3W | 700mA | 2600 lm | 112 lm/W | 98 | A+ |
| | 65,8W | 1750mA | 5570 lm | 85 lm/W | 98 | A+ |
| 3000K | 23,3W | 700mA | 2840 lm | 122 lm/W | 98 | A+ |
| | 65,8W | 1750mA | 6100 lm | 93 lm/W | 98 | A+ |

ORDER REFERENCE

> [FIXTURE](#)

! ORDER REFERENCE + W (white) / B (black)

2700K

HE 700mA

| | | |
|------------|-------------------|--|
| 16° | ZUMI01102ART02082 | Cannon Art SLE G5 HE 23,3W 700mA 2600 lm 2700K CRI98 16° glass excl. conv. |
| 26° | ZUMI01102ART03082 | Cannon Art SLE G5 HE 23,3W 700mA 2600 lm 2700K CRI98 26° glass excl. conv. |
| 42° | ZUMI01102ART04082 | Cannon Art SLE G5 HE 23,3W 700mA 2600 lm 2700K CRI98 42° glass excl. conv. |

HO 1750mA

| | | |
|------------|-------------------|---|
| 16° | ZUMI01102ART02112 | Cannon Art SLE G5 HO 65,8W 1750mA 5570 lm 2700K CRI98 16° glass excl. conv. |
| 26° | ZUMI01102ART03112 | Cannon Art SLE G5 HO 65,8W 1750mA 5570 lm 2700K CRI98 26° glass excl. conv. |
| 42° | ZUMI01102ART04112 | Cannon Art SLE G5 HO 65,8W 1750mA 5570 lm 2700K CRI98 42° glass excl. conv. |

3000K

HE 700mA

| | | |
|------------|-------------------|--|
| 16° | ZUMI01013ART02082 | Cannon Art SLE G5 HE 23,3W 700mA 2840 lm 3000K CRI98 16° glass excl. conv. |
| 26° | ZUMI01013ART03082 | Cannon Art SLE G5 HE 23,3W 700mA 2840 lm 3000K CRI98 26° glass excl. conv. |
| 42° | ZUMI01013ART04082 | Cannon Art SLE G5 HE 23,3W 700mA 2840 lm 3000K CRI98 42° glass excl. conv. |

HO 1750mA

| | | |
|------------|-------------------|---|
| 16° | ZUMI01013ART02112 | Cannon Art SLE G5 HO 65,8W 1750mA 6100 lm 3000K CRI98 16° glass excl. conv. |
| 26° | ZUMI01013ART03112 | Cannon Art SLE G5 HO 65,8W 1750mA 6100 lm 3000K CRI98 26° glass excl. conv. |
| 42° | ZUMI01013ART04112 | Cannon Art SLE G5 HO 65,8W 1750mA 6100 lm 3000K CRI98 42° glass excl. conv. |

> CONVERTER*HE 700mA***dimmable**

ZUMI28000125278

LCAI 35W 700mA ECO SR + I SELECT PLUG (DALI, DSI, switchDIM)

non dimmable

TRID24166314

LCI 30W 700mA IP20

*HO 1750mA***dimmable**

ZUMI28000256274

LCAI 100W 1750mA ECO SR + I SELECT PLUG + LCF 12V Fandr. (DALI, DSI, switchDIM)

non dimmable

ZUMI28000204274

LCI 100W 1750mA TOP SR + I SELECT PLUG +LCF 12V Fandriver

> OPTIONS**PC-cover**

ZUMI010000000500

PC-cover for food environment Ø 111

Flat Springs

ZUMIFS

Flat Springs

Emergency kit

On request