


PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting.
Aluminium fixture, white or black powder coated, with several possible reflectors (16°, 26°, 42°).

The PI-LED-version makes it possible to change color from 2500K to 7000K but also to create all additional RGB-colors. This way any atmosphere can be created. Available in two different versions: the low output (350mA) or the high output (500mA) version.

Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø150mm h170mm
IP rating	IP20
Power	48V
Lifetime L70/F10/65°C	50000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2500K-7000K RGB LO	22W	350mA	2300 lm	100 lm/W	90+	A+
2500K-7000K RGB HO	31W	500mA	3000 lm	96 lm/W	90+	A+

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + W (white) / B (black)

LO 22W

DALI

16°	ZUMI01131PI02062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 16° glass excl. conv. dim DALI (Only DT8)
26°	ZUMI01131PI03062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 26° glass excl. conv. dim DALI (Only DT8)
42°	ZUMI01131PI04062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 42° glass excl. conv. dim DALI (Only DT8)

ZigBee

16°	ZUMI01132PI02062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 16° glass excl. conv. dim ZigBee
26°	ZUMI01132PI03062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 26° glass excl. conv. dim ZigBee
42°	ZUMI01132PI04062	Cannon PI-LED LO 22W 48V 2300 lm CRI90+ 42° glass excl. conv. dim ZigBee

HO 31W

DALI

16°	ZUMI01133PI02062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 16° glass excl. conv. dim DALI (Only DT8)
26°	ZUMI01133PI03062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 26° glass excl. conv. dim DALI (Only DT8)
42°	ZUMI01133PI04062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 42° glass excl. conv. dim DALI (Only DT8)

ZigBee

16°	ZUMI01134PI02062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 16° glass excl. conv. dim ZigBee
26°	ZUMI01134PI03062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 26° glass excl. conv. dim ZigBee
42°	ZUMI01134PI04062	Cannon PI-LED HO 31W 48V 3000 lm CRI90+ 42° glass excl. conv. dim ZigBee

> CONVERTER - REQUIRED!**350/500mA - 48V**

LUMILTP-1033-V01

LED Driver for PI-LED Systems 60W/48V

> CONTROLLER**ZigBee** ZUMI

ZigBee Controller

> OPTIONS**PC-cover**

ZUMI010000000500

PC-cover for food environment Ø 111

Flat Springs

ZUMIFS

Flat Springs