

PRODUCT DESCRIPTION


The mini version of the cannon, a recessed downlighter for general or accent lighting. Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).

Standard equipped with torsion springs.

TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø110mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2400K	13,5W	350mA	798 lm	59 lm/W	/	A
2700K	13,5W	350mA	1470 lm	109 lm/W	80	A++
3000K	13,5W	350mA	1525 lm	113 lm/W	80	A++
3500K	13,5W	350mA	1587 lm	118 lm/W	80	A++
4000K	13,5W	350mA	1600 lm	119 lm/W	80	A++

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector) option only for 2400K, 2700K or 3000K

2400K

25°	ZUMI2611592415062	Cannon Mini Gold+ SLE G5 13,5W 350mA 798 lm 2400K 25° glass excl. conv.
39°	ZUMI2611592416062	Cannon Mini Gold+ SLE G5 13,5W 350mA 798 lm 2400K 39° glass excl. conv.
61°	ZUMI2611592417062	Cannon Mini Gold+ SLE G5 13,5W 350mA 798 lm 2400K 61° glass excl. conv.

2700K

25°	ZUMI2610082715062	Cannon Mini Classic SLE G5 13,5W 350mA 1470 lm 2700K CRI80 25° glass - excl. conv.
39°	ZUMI2610082716062	Cannon Mini Classic SLE G5 13,5W 350mA 1470 lm 2700K CRI80 39° glass - excl. conv.
61°	ZUMI2610082717062	Cannon Mini Classic SLE G5 13,5W 350mA 1470 lm 2700K CRI80 61° glass - excl. conv.

3000K

25°	ZUMI2609483015062	Cannon Mini Classic SLE G5 13,5W 350mA 1525 lm 3000K CRI80 25° glass - excl. conv.
39°	ZUMI2609483016062	Cannon Mini Classic SLE G5 13,5W 350mA 1525 lm 3000K CRI80 39° glass - excl. conv.
61°	ZUMI2609483017062	Cannon Mini Classic SLE G5 13,5W 350mA 1525 lm 3000K CRI80 61° glass - excl. conv.

3500K

25°	ZUMI2610883515062	Cannon Mini Classic SLE G5 13,5W 350mA 1587 lm 3500K CRI80 25° glass - excl. conv.
39°	ZUMI2610883516062	Cannon Mini Classic SLE G5 13,5W 350mA 1587 lm 3500K CRI80 39° glass - excl. conv.
61°	ZUMI2610883517062	Cannon Mini Classic SLE G5 13,5W 350mA 1587 lm 3500K CRI80 61° glass - excl. conv.

4000K

25°	ZUMI2609584015062	Cannon Mini Classic SLE G5 13,5W 350mA 1600 lm 4000K CRI80 25° glass - excl. conv.
39°	ZUMI2609584016062	Cannon Mini Classic SLE G5 13,5W 350mA 1600 lm 4000K CRI80 39° glass - excl. conv.
61°	ZUMI2609584017062	Cannon Mini Classic SLE G5 13,5W 350mA 1600 lm 4000K CRI80 61° glass - excl. conv.

> CONVERTER**dimmable**

TRID28000123

LCAI 20W 350mA ECO SR (DALI, DSI, switchDIM)

non dimmable

TRID87500187

LCI 20W 350mA TEC SR

> OPTIONS**PC-cover**

ZUMI2600000500

PC-cover for food environment - Ø 71

Flat Springs

ZUMIFS

Flat Springs

Emergency kit

On request