

PRODUCT DESCRIPTION


The mini version of the cannon, a recessed downlighter for general or accent lighting. Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).

Standard equipped with torsion springs.

TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø107mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2400K	11,8W	350mA	1029 lm	88 lm/W	/	A
2700K	11,8W	350mA	1855 lm	158 lm/W	80+	A++
3000K	11,8W	350mA	1904 lm	162 lm/W	80+	A++
3500K	11,8W	350mA	1939 lm	165 lm/W	80+	A++
4000K	11,8W	350mA	1981 lm	168 lm/W	80+	A++

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
 + (2) **G** (gold reflector) option only for 2400K, 2700K or 3000K

2400K

- 25° ZUMI2611592415062 Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 25° glass excl. conv.
- 39° ZUMI2611592416062 Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 39° glass excl. conv.
- 61° ZUMI2611592417062 Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 61° glass excl. conv.

2700K

- 25° ZUMI2610082715062 Cannon Mini Classic SLE G6 11,8W 350mA 1855 lm 2700K CRI80 25° glass - excl. conv.
- 39° ZUMI2610082716062 Cannon Mini Classic SLE G6 11,8W 350mA 1855 lm 2700K CRI80 39° glass - excl. conv.
- 61° ZUMI2610082717062 Cannon Mini Classic SLE G6 11,8W 350mA 1855 lm 2700K CRI80 61° glass - excl. conv.

3000K

- 25° ZUMI2609483015062 Cannon Mini Classic SLE G6 11,8W 350mA 1904 lm 3000K CRI80 25° glass - excl. conv.
- 39° ZUMI2609483016062 Cannon Mini Classic SLE G6 11,8W 350mA 1904 lm 3000K CRI80 39° glass - excl. conv.
- 61° ZUMI2609483017062 Cannon Mini Classic SLE G6 11,8W 350mA 1904 lm 3000K CRI80 61° glass - excl. conv.

3500K

- 25° ZUMI2610883515062 Cannon Mini Classic SLE G6 11,8W 350mA 1939 lm 3500K CRI80 25° glass - excl. conv.
- 39° ZUMI2610883516062 Cannon Mini Classic SLE G6 11,8W 350mA 1939 lm 3500K CRI80 39° glass - excl. conv.
- 61° ZUMI2610883517062 Cannon Mini Classic SLE G6 11,8W 350mA 1939 lm 3500K CRI80 61° glass - excl. conv.

4000K

- 25° ZUMI2609584015062 Cannon Mini Classic SLE G6 11,8W 350mA 1981 lm 4000K CRI80 25° glass - excl. conv.
- 39° ZUMI2609584016062 Cannon Mini Classic SLE G6 11,8W 350mA 1981 lm 4000K CRI80 39° glass - excl. conv.
- 61° ZUMI2609584017062 Cannon Mini Classic SLE G6 11,8W 350mA 1981 lm 4000K CRI80 61° glass - excl. conv.

> CONVERTER**dimmable**

TRID28000670 + TRID28001110

LCA 17W 250-700mA one4all SR PRE + PLUG 350mA (DALI, DSI, switchDIM)

non dimmable

TRID87500621

LC 20W 350/500/700mA flexC SR ADV

> OPTIONS**PC-cover**

ZUMI2600000500

PC-cover for food environment - Ø 71

Flat Springs

ZUMIFS

Flat Springs

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon. A recessed downlighter for general or accent lighting with a CRI of 90 for a better color accuracy.

Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø107mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	11,8W	350mA	1568 lm	133 lm/W	90+	A+
3000K	11,8W	350mA	1610	137 lm/W	90+	A++
3500K	11,8W	350mA	1680 lm	143 lm/W	90+	A++
4000K	11,8W	350mA	1729 lm	147 lm/W	90+	A++

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
 + (2) **G** (gold reflector) option only for 2700K or 3000K

2700K

- 25° ZUMI2610992715062 Cannon Mini Select SLE G6 11,8W 350mA 1568 lm 2700K CRI90 25° glass - excl.conv.
- 39° ZUMI2610992716062 Cannon Mini Select SLE G6 11,8W 350mA 1568 lm 2700K CRI90 39° glass - excl.conv.
- 61° ZUMI2610992717062 Cannon Mini Select SLE G6 11,8W 350mA 1568 lm 2700K CRI90 61° glass - excl.conv.

3000K

- 25° ZUMI2611093015062 Cannon Mini Select SLE G6 11,8W 350mA 1610 lm 3000K CRI90 25° glass - excl.conv.
- 39° ZUMI2611093016062 Cannon Mini Select SLE G6 11,8W 350mA 1610 lm 3000K CRI90 39° glass - excl.conv.
- 61° ZUMI2611093017062 Cannon Mini Select SLE G6 11,8W 350mA 1610 lm 3000K CRI90 61° glass - excl.conv.

3500K

- 25° ZUMI2611193515062 Cannon Mini Select SLE G6 11,8W 350mA 1680 lm 3500K CRI90 25° glass - excl.conv.
- 39° ZUMI2611193516062 Cannon Mini Select SLE G6 11,8W 350mA 1680 lm 3500K CRI90 39° glass - excl.conv.
- 61° ZUMI2611193517062 Cannon Mini Select SLE G6 11,8W 350mA 1680 lm 3500K CRI90 61° glass - excl.conv.

4000K

- 25° ZUMI2611292715062 Cannon Mini Select SLE G6 11,8W 350mA 1729 lm 4000K CRI90 25° glass - excl.conv.
- 39° ZUMI2611292716062 Cannon Mini Select SLE G6 11,8W 350mA 1729 lm 4000K CRI90 39° glass - excl.conv.
- 61° ZUMI2611292717062 Cannon Mini Select SLE G6 11,8W 350mA 1729 lm 4000K CRI90 61° glass - excl.conv.

> CONVERTER**dimmable**

TRID28000670 + TRID28001110 LCA 17W 250-700mA one4all SR PRE + PLUG 350mA (DALI, DSI, switchDIM)

non dimmable

TRID87500621 LC 20W 350/500/700mA flexC SR ADV

> OPTIONS**PC-cover**

ZUMI2600000500 PC-cover for food environment - Ø 71

Flat Springs

ZUMIFS Flat Springs

Emergency kit


On request

PRODUCT DESCRIPTION

The mini version of the cannon, equipped with a LEDmodule especially to enlighten several food products. There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes. The cannon 'meat+' provides a highly red color which is ideal for the presentation of meat. Its relative 'fresh meat' is suitable to use for meat in the counter.

Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).

Standard equipped with PC-cover for food environment and torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: Ø107mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3 (GOLD+ / FRESH MEAT: 4)
Guarantee	5 year
(*on components, only if ordered luminaire + driver)	

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
*FISH	11,8W	350mA	1624 lm	138 lm/W	/	A++
GOLD 2700K	11,8W	350mA	1421 lm	121 lm/W	80	A+
GOLD+ 2400K	11,8W	350mA	1029 lm	88 lm/W	/	A
*MEAT+	11,8W	350mA	1001 lm	85 lm/W	/	A
*FRESH MEAT	11,8W	350mA	938 lm	79 lm/w	/	A

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + W (white) / B (black)

FISH

25°	ZUMI26113FI19062	Cannon Mini Fish SLE G6 11,8W 350mA 1624 lm 25° PC excl. conv.
39°	ZUMI26113FI20062	Cannon Mini Fish SLE G6 11,8W 350mA 1624 lm 39° PC excl. conv.
61°	ZUMI26113FI21062	Cannon Mini Fish SLE G6 11,8W 350mA 1624 lm 61° PC excl. conv.

GOLD 2700K

25°	ZUMI2611495219062	Cannon Mini Gold SLE G6 11,8W 350mA 1421 lm 2700K CRI80 25° PC excl. conv.
39°	ZUMI2611495220062	Cannon Mini Gold SLE G6 11,8W 350mA 1421 lm 2700K CRI80 39° PC excl. conv.
61°	ZUMI2611495221062	Cannon Mini Gold SLE G6 11,8W 350mA 1421 lm 2700K CRI80 61° PC excl. conv.

GOLD+ 2400K

25°	ZUMI2611592419062	Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 25° PC excl. conv.
39°	ZUMI2611592420062	Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 39° PC excl. conv.
61°	ZUMI2611592421062	Cannon Mini Gold+ SLE G6 11,8W 350mA 1029 lm 2400K 61° PC excl. conv.

MEAT+

25°	ZUMI26116CM+19062	Cannon Mini Meat+ SLE G6 11,8W 350mA 1001 lm 25° PC excl. conv.
39°	ZUMI26116CM+20062	Cannon Mini Meat+ SLE G6 11,8W 350mA 1001 lm 39° PC excl. conv.
61°	ZUMI26116CM+21062	Cannon Mini Meat+ SLE G6 11,8W 350mA 1001 lm 61° PC excl. conv.

FRESH MEAT

25°	ZUMI26117FM19062	Cannon Mini Fresh Meat SLE G6 11,8W 350mA 938 lm 25° PC excl. conv.
39°	ZUMI26117FM20062	Cannon Mini Fresh Meat SLE G6 11,8W 350mA 938 lm 39° PC excl. conv.
61°	ZUMI26117FM21062	Cannon Mini Fresh Meat SLE G6 11,8W 350mA 938 lm 61° PC excl. conv.

> CONVERTER**dimmable**

TRID28000670 + TRID28001110 LCA 17W 250-700mA one4all SR PRE + PLUG 350mA (DALI, DSI, switchDIM)

non dimmable

TRID87500621 LC 20W 350/500/700mA flexC SR ADV

> OPTIONS**Flat Springs**

ZUMIFS Flat Springs

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The art version is with its CRI 98 the perfect solution to enlighten art and musea.

Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø107mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	2
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3000K	11,8W	350mA	1400 lm	119 lm/W	98	A+

ORDER REFERENCE

> [FIXTURE](#)

! ORDER REFERENCE + W (white) / B (black)

3000K

25°	ZUMI26099ART15062	Cannon Mini Art SLE G6 11,8W 350mA 1400 lm 3000K CRI98 25° glass excl. conv.
39°	ZUMI26099ART16062	Cannon Mini Art SLE G6 11,8W 350mA 1400 lm 3000K CRI98 39° glass excl. conv.
61°	ZUMI26099ART17062	Cannon Mini Art SLE G6 11,8W 350mA 1400 lm 3000K CRI98 61° glass excl. conv.

> [CONVERTER](#)

dimmable

TRID28000670 + TRID28001110 LCA 17W 250-700mA one4all SR PRE + PLUG 350mA (DALI, DSI, switchDIM)

non dimmable

TRID87500621 LC 20W 350/500/700mA flexC SR ADV

> [OPTIONS](#)

PC-cover

ZUMI2600000500 PC-cover for food environment - ø 71

Flat Springs

ZUMIFS Flat Springs

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The fashion version has an optimized light spectrum with warm, lively colours combined with a pure, shiny white, which is ideal for the perfect fashion presentation.

Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: Ø107mm h110mm
IP rating	IP20
Power	350mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	11,8W	350mA	1463 lm	124 lm/W	95	A+

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + W (white) / B (black)

3250K

25°	ZUMI2611893215062	Cannon Mini Fashion SLE G6 11,8W 350mA 1463 lm 3250K CRI95 25° glass excl.conv.
39°	ZUMI2611893216062	Cannon Mini Fashion SLE G6 11,8W 350mA 1463 lm 3250K CRI95 39° glass excl.conv.
61°	ZUMI2611893217062	Cannon Mini Fashion SLE G6 11,8W 350mA 1463 lm 3250K CRI95 61° glass excl.conv.

> CONVERTER

dimmable

TRID28000670 + TRID28001110	LCA 17W 250-700mA one4all SR PRE + PLUG 350mA (DALI, DSI, switchDIM)
-----------------------------	--

non dimmable

TRID87500621	LC 20W 350/500/700mA flexC SR ADV
--------------	-----------------------------------

> OPTIONS

PC-cover

ZUMI2600000500	PC-cover for food environment - Ø 71
----------------	--------------------------------------

Flat Springs

ZUMIFS	Flat Springs
--------	--------------

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The cannon mini tunable white has a color temperature range from 2700K up to 6500K.

Aluminium fixture, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: ø107mm h110mm
IP rating	IP20
Power	500mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K - 6500K	22,2W	500mA	1350 lm	61 lm/W	90+	A

ORDER REFERENCE

> FIXTURE

! ORDER REFERENCE + W (white) / B (black)

TW		
39°	ZUMI26123TW16072	Cannon mini TW SLE1400 PRE 1350 lm 22,2W 2700-6500K CRI90+ 39° glass excl. conv.
61°	ZUMI26123TW17072	Cannon mini TW SLE1400 PRE 1350 lm 22,2W 2700-6500K CRI90+ 61° glass excl. conv.

> CONVERTER - REQUIRED!

dimmable
 ZUMI86459108TW LCAU 2x020/0048 one4all + RJ45U1M + CON. CABLE + SR SET
 dimmable DALI (only Device Type 8) , DSI, switchDIM


Control via switchDIM:

A conventional double pushbutton switch can be used for control via switchDIM. One of the pushbuttons is used to set the colour temperature, the other to set the dimming level.

For control via a switchDIM switch different settings can be made:


- Setting for the colour temperature via colourTEMPERATURE mode or colourSWITCH mode with 8 predefined values 2,700 K and 6,500 K.
- Stepless setting for the dimming level between 15 and 100 %.

colourTEMPERATURE



- 1- 2700K
- 2- 3000K
- 3- 3500K
- 4- 4000K
- 5- 4200K
- 6- 5000K
- 7- 5700K
- 8- 6500K

colourSWITCH



- 1- Gold 2700K- bread and cakes
- 2- 2800K- fruit and vegetables
- 3- 3000K
- 4- Fish
- 5- Cheese Yellow
- 6- 5000K
- 7- Cool Meat
- 8- Cool Meat+

> OPTIONS

PC-cover

ZUMI2600000500

PC-cover for food environment - Ø 71

Flat Springs

ZUMIFS

Flat Springs