



# °ledline 60

177

material	anodised aluminium coated
weight	2,5 kg/m - 1,65 lb/ft
voltage	110-240 Vac
cri	>90
wattage	28W / meter
dali	supported DT6 option
certifications	CE ENEC
classifications	IP20 



<b>LL60.L.B.T.K.D</b>		led modules cuttable every 8 cm
Length	<b>2000</b> <b>100 - ...</b>	standard length custom length
Body color	<b>BK</b> <b>WH</b> <b>AL</b>	black matt ral 9011 white matt ral 9016 aluminium color anodised (on request only)
Type	<b>SM</b> <b>PD</b>	surface mount pendant
<b>K</b>	<b>WW.28</b> <b>WW2.28</b> <b>NW2.28</b> <b>TW</b>	2700K   28W   1650 lm/m 3000K   28W   1780 lm/m 4000K   28W   1850 lm/m tunable white - on request
Driver (integrated)	<b>ND</b> <b>DA</b> <b>DA2</b> <b>10V</b>	Non dimmable 100-240VAC DALI 220-240VAC DALI 100-240VAC 1-10V 100-240VAC
Accessories	<b>LL60.EC.BK</b> <b>LL60.EC.WH</b> <b>LL60.EC.AL</b>  <b>LL60.MC.ST</b> <b>LL60.MC.90</b>	led line 25 End Cap Black led line 25 End Cap White led line 25 End Cap Aluminium  Mechanical Connector plate Straight Mechanical Connector plate 90°