



Light efficiency:



Light quality:



Color temperature:



Product name:

turn plus 25deg 3000K


Item number:

Date and time:


1/02/2020 14:26:39

Output: 881 Lumen Power consumption: 13,0


Spectral distribution




Color coordinates



White color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3208 K	91,6	50,8	90,0	98,3	90,0	0,420	0,391	0,245	0,342	-0,0026

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
25,5°	51,6°	64,5°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
3333 cd	95,9%	95,0%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
3333lx	833lx	370lx	208lx	133lx	93lx	68lx	52lx	41lx	33lx	28lx	23lx	20lx	17lx	15lx	13lx	12lx	10lx	9lx	8lx
309,6fcd	77,4fcd	34,4fcd	19,4fcd	12,4fcd	8,6fcd	6,3fcd	4,8fcd	3,8fcd	3,1fcd	2,6fcd	2,2fcd	1,8fcd	1,6fcd	1,4fcd	1,2fcd	1,1fcd	1fcd	0,9fcd	0,8fcd

Power scope

Power	Power factor	Power frequency
13,0 W	0,9	{FREQ } Hz

Nominal voltage	Voltage	Current
230 V	48,0 V	0,270 A