


PRODUCT DESCRIPTION


Adjustable recessed downlighter for general or accent lighting.
 Aluminium fixture, white or black powder coated, provided with a LEDmodule which replaces the MR16 halogen spotlight. Available in 2700, 3000 and 4000K and in a low output (250mA) and high output (350mA) version.

TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: torsion springs: ø86mm h100mm flat springs: ø83mm h100mm
IP rating	IP20
Power	250/350mA
Lifetime L70/B10/65°C	250mA: 42000h / 350mA: >50000h
MacAdam ellipse	3
Guarantee	3 year



ROVA SLA 700



ROVA SLA 1200

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	A+
	12,2W	350mA	1140 lm	93 lm/W	90+	A+
3000K	8,8W	250mA	840 lm	95 lm/W	90+	A+
	12,2W	350mA	1170 lm	96 lm/W	90+	A+
4000K	8,8W	250mA	890 lm	101 lm/W	90+	A++
	12,2W	350mA	1270 lm	104 lm/W	90+	A++

ORDER REFERENCE> Fixture**ORDER REFERENCE + W (white) / B (black)****2700K***700lm*

- 24°** ZUMI3816892715142 Rori 700 DC 8,8W 250mA 770 lm 2700K CRI90 24° excl. conv.
36° ZUMI3816992716142 Rori 700 DC 8,8W 250mA 770 lm 2700K CRI90 36° excl. conv.

1200lm

- 24°** ZUMI3816292715062 Rori 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 24° excl. conv.
36° ZUMI3816392716062 Rori 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 36° excl. conv.

3000K*700lm*

- 24°** ZUMI3817093015142 Rori 700 DC 8,8W 250mA 840 lm 3000K CRI90 24° excl. conv.
36° ZUMI3817193016142 Rori 700 DC 8,8W 250mA 840 lm 3000K CRI90 36° excl. conv.

1200lm

- 24°** ZUMI3816493015062 Rori 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 24° excl. conv.
36° ZUMI3816593016062 Rori 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 36° excl. conv.

4000K*700lm*

- 24°** ZUMI3817294015142 Rori 700 DC 8,8W 250mA 890 lm 4000K CRI90 24° excl. conv.
36° ZUMI3817394016142 Rori 700 DC 8,8W 250mA 890 lm 4000K CRI90 36° excl. conv.

1200lm

- 24°** ZUMI3816694015062 Rori 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 24° excl. conv.
36° ZUMI3816794016062 Rori 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 36° excl. conv.

> CONVERTER

250mA

dimmable

TRID87500627

or TRID28000669 + PLUG TRID28001106

non dimmable

TRID87500580

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

LCA 10W 150-400mA one4all SR PRE (DALI, DSI, switchDIM)

350mA

dimmable

TRID87500627

or TRID28000670 + PLUG TRID28001110

non dimmable

TRID24166312

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

LCA 17W 250-700mA one4all SR PRE (DALI, DSI, switchDIM)

LCI 15W 350mA IP20

> OPTIONS**Flat Springs**

ZUMIFS

Flat Springs