

PRODUCT DESCRIPTION


The TUBB S80 is a rotatable spot placed on a plate with a diameter of 80mm for general or accent lighting. Aluminium luminaire in several colors and color temperatures with several possible reflectors.

TECHNICAL DATA

Application semi-recessed
 Dimensions cut out ø 60mm h 60mm
 IP rating IP20
 Power 350mA / 500mA
 Lifetime L70/F10/65°C >55000h
 MacAdam ellipse 2
 Guarantee 5 year
 (*on components, only if ordered luminaire **+driver**)



80



80

Color Temperature	Wattage excl. driver	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	11,8W	350mA	1313 lm	136 lm/W	95	F	F
	16,9W	500mA	1876 lm	136 lm/W	95	F	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) W (white) / B (black) / G (gold) / F (forest)

14°	ZUMI722232317	Tubb S80 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 14° glass excl. driver
25°	ZUMI722232417	Tubb S80 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 25° glass excl. driver
39°	ZUMI722232517	Tubb S80 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 39° glass excl. driver
61°	ZUMI722232617	Tubb S80 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 61° glass excl. driver

> DRIVER

dimmable

TRID28000675 LCA 25W 350-1050mA one4all SC PRE (DALI, DSI, switchDIM)
 + TRID28001168 Strain-relief
 + TRID28001110 PLUG 350mA
 of
 + TRID28001114 PLUG 500mA

non dimmable

TRID28000706 LC 25W 350-1050mA flexC SC EXC
 + TRID28001168 Strain-relief
 + TRID28001110 PLUG 350mA
 of
 + TRID28001114 PLUG 500mA

OPTIONS

Honeycomb grid

ZUMI25HC Honeycomb grid