


PRODUCT DESCRIPTION

Surface downlighter for general or accent lighting.
Aluminium luminaire in several colors and color temperatures with several possible reflectors.

TECHNICAL DATA

Application	Surface
Dimensions	ø 80mm h 110mm
IP rating	IP20
Power	230V or 350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	11,8W	13,6W	350mA	1558 lm	134 lm/W	90+	E
	16,9W	19,4W	500mA	2225 lm	134 lm/W	90+	E
3000K	11,8W	13,6W	350mA	1714 lm	147 lm/W	90+	E
	16,9W	19,4W	500mA	2449 lm	147 lm/W	90+	E
3500K	11,8W	13,6W	350mA	1732 lm	149 lm/W	90+	E
	16,9W	19,4W	500mA	2474 lm	149 lm/W	90+	E
4000K	11,8W	13,6W	350mA	1775 lm	152 lm/W	90+	E
	16,9W	19,4W	500mA	2536 lm	152 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
+ (2) **G** (gold reflector) option only for 2700K or 3000K

DRIVER INCLUDED - 350mA - non dimmable**2700K**

14°	ZUMI652132306	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 14° glass incl. driver
25°	ZUMI652132406	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 25° glass incl. driver
39°	ZUMI652132506	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 39° glass incl. driver
61°	ZUMI652132606	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 61° glass incl. driver

3000K

14°	ZUMI652142306	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 14° glass incl. driver
25°	ZUMI652142406	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 25° glass incl. driver
39°	ZUMI652142506	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 39° glass incl. driver
61°	ZUMI652142606	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 61° glass incl. driver

3500K

14°	ZUMI652152306	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 14° glass incl. driver
25°	ZUMI652152406	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 25° glass incl. driver
39°	ZUMI652152506	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 39° glass incl. driver
61°	ZUMI652152606	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 61° glass incl. driver

4000K

14°	ZUMI652162306	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 14° glass incl. driver
25°	ZUMI652162406	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 25° glass incl. driver
39°	ZUMI652162506	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 39° glass incl. driver
61°	ZUMI652162606	Tubb Surface CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 61° glass incl. driver

DRIVER EXCLUDED - 350mA/500mA**2700K**

14°	ZUMI652132317	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI652132417	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 25° glass excl. driver
39°	ZUMI652132517	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 39° glass excl. driver
61°	ZUMI652132617	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 61° glass excl. driver

3000K

14°	ZUMI652142317	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 14° glass excl. driver
25°	ZUMI652142417	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 25° glass excl. driver
39°	ZUMI652142517	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 39° glass excl. driver
61°	ZUMI652142617	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 61° glass excl. driver

3500K

14°	ZUMI652152317	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 14° glass excl. driver
25°	ZUMI652152417	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 25° glass excl. driver
39°	ZUMI652152517	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 39° glass excl. driver
61°	ZUMI652152617	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 61° glass excl. driver

4000K

14°	ZUMI652162317	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 14° glass excl. driver
25°	ZUMI652162417	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 25° glass excl. driver
39°	ZUMI652162517	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 39° glass excl. driver
61°	ZUMI652162617	Tubb Surface CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 61° glass excl. driver

> DRIVER**dimmable**

TRID28000671	LCA 25W 350-1050mA one4all SR PRE (DALI, DSI, switchDIM)
+TRID28001110	PLUG 350mA
of	
+TRID28001114	PLUG 500mA

non dimmable

TRID28000700	LC 25W 350-1050mA flexC SR EXC
+TRID28001110	PLUG 350mA
of	
+TRID28001114	PLUG 500mA

> OPTIONS**Honeycomb grid**