

PRODUCT DESCRIPTION


Surface mounted spot for general or accent lighting with a CRI of 90 for a better color accuracy.

Aluminium luminaire, white or black powder coated, available in different color temperatures, with several possible reflectors (16°, 26°, 42°).



TECHNICAL DATA

Application	surface
Dimensions	∅ 120mm h 150mm - base 150 x 96 x 40mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	36,7W	900mA	3801 lm	121 lm/W	90+	E
3000K	36,7W	900mA	4175 lm	133 lm/W	90+	E
4000K	36,7W	900mA	4369 lm	140 lm/W	90+	D

ORDER REFERENCE

> [LUMINAIRE](#)

- ! **ORDER REFERENCE** + (1) **W** (white) / **B** (black)
- + (2) **G** (gold reflector) option only for 2700K or 3000K
- + (3) **DD** (for DALI dimmable)

2700K

16°	ZUMI911960221	Slingshot base SLE G7 HO 3801 lm 900mA 36,7W 2700K CRI90+ 16° incl.driver
26°	ZUMI911960321	Slingshot base SLE G7 HO 3801 lm 900mA 36,7W 2700K CRI90+ 26° incl.driver
40°	ZUMI911960421	Slingshot base SLE G7 HO 3801 lm 900mA 36,7W 2700K CRI90+ 42° incl.driver

3000K

16°	ZUMI911970221	Slingshot base SLE G7 HO 4175 lm 900mA 36,7W 3000K CRI90+ 16° incl.driver
26°	ZUMI911970321	Slingshot base SLE G7 HO 4175 lm 900mA 36,7W 3000K CRI90+ 26° incl.driver
40°	ZUMI911970421	Slingshot base SLE G7 HO 4175 lm 900mA 36,7W 3000K CRI90+ 42° incl.driver

4000K

16°	ZUMI911990221	Slingshot base SLE G7 HO 4369 lm 900mA 36,7W 4000K CRI90+ 16° incl.driver
26°	ZUMI911990321	Slingshot base SLE G7 HO 4369 lm 900mA 36,7W 4000K CRI90+ 26° incl.driver
40°	ZUMI911990421	Slingshot base SLE G7 HO 4369 lm 900mA 36,7W 4000K CRI90+ 42° incl.driver

> [DRIVER](#)

Included, if dimmable: DALI, pushDIM.

> [OPTIONS](#)

PC cover

ZUMI01000000500	PC-cover for food environment ∅ 111
-----------------	-------------------------------------