


PRODUCT DESCRIPTION

A mini version of the slingshot. Spot on track for general or accent lighting with a CRI of >90 for a better color accuracy.

Aluminium luminaire, white or black powder coated, available in different color temperatures, with several possible reflectors (25°, 39°, 61°).

TECHNICAL DATA

Application	3F track
Dimensions	∅ 80mm h 130mm - base 130 x 60 x 40mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	19,4W	500mA	2225 lm	134 lm/W	90+	E
3000K	19,4W	500mA	2449 lm	147 lm/W	90+	E
3500K	19,4W	500mA	2474 lm	149 lm/W	90+	E
4000K	19,4W	500mA	2536 lm	152 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
 + (2) **G** (gold reflector) option only for 2700K or 3000K
 + (3) **DD1** (for DALI dim.Eutrac) / **DD2** (for DALI dim. Global) / **PD** (for dimmable phase cut)

2700K

25°	ZUMI252131507	Slingshot Mini 3F SLE G7 2225 lm 500mA 19,4W 2700K CRI90+ 25° incl.driver
39°	ZUMI252131607	Slingshot Mini 3F SLE G7 2225 lm 500mA 19,4W 2700K CRI90+ 39° incl.driver
61°	ZUMI252131707	Slingshot Mini 3F SLE G7 2225 lm 500mA 19,4W 2700K CRI90+ 61° incl.driver

3000K

25°	ZUMI252141507	Slingshot Mini 3F SLE G7 2449lm 500mA 19,4W 3000K CRI90+ 25° incl.driver
39°	ZUMI252141607	Slingshot Mini 3F SLE G7 2449lm 500mA 19,4W 3000K CRI90+ 39° incl.driver
61°	ZUMI252141707	Slingshot Mini 3F SLE G7 2449lm 500mA 19,4W 3000K CRI90+ 61° incl.driver

3500K

25°	ZUMI252151507	Slingshot Mini 3F SLE G7 2474lm 500mA 19,4W 3500K CRI90+ 25° incl.driver
39°	ZUMI252151607	Slingshot Mini 3F SLE G7 2474lm 500mA 19,4W 3500K CRI90+ 39° incl.driver
61°	ZUMI252151707	Slingshot Mini 3F SLE G7 2474lm 500mA 19,4W 3500K CRI90+ 61° incl.driver

4000K

25°	ZUMI252161507	Slingshot Mini 3F SLE G7 2536lm 500mA 19,4W 3000K CRI90+ 25° incl.driver
39°	ZUMI252161607	Slingshot Mini 3F SLE G7 2536lm 500mA 19,4W 3000K CRI90+ 39° incl.driver
61°	ZUMI252161707	Slingshot Mini 3F SLE G7 2536lm 500mA 19,4W 3000K CRI90+ 61° incl.driver

> DRIVER

Included, if dimmable: DALI or phase cut

> OPTIONS

PC-cover	ZUMI2600000500	PC-cover for food environment - ∅ 71
Grid	ZUMI25HC	Honeycomb grid