


PRODUCT DESCRIPTION

Spot on track for general or accent lighting with a CRI of 90+ for a better color accuracy.

Aluminium luminaire, white or black powder coated, available in different color temperatures, with several possible reflectors (16°, 26°, 40°).

TECHNICAL DATA

Application	3F track
Dimensions	∅ 120mm h 150mm - base 150 x 96 x 40mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	36,7W	900mA	3801 lm	121 lm/W	90+	E
3000K	36,7W	900mA	4175 lm	133 lm/W	90+	E
4000K	36,7W	900mA	4369 lm	140 lm/W	90+	D

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
 + (2) **G** (gold reflector) option only for 2700K or 3000K
 + (3) **DD1** (for DALI dim.Eutrac) / **DD2** (for DALI dim. Global)

2700K

16° ZUMI041960221 Slingshot 3F SLE G7 36,7W 900mA 3801 lm 2700K CRI90+ 16° glass incl.driver
 26° ZUMI041960321 Slingshot 3F SLE G7 36,7W 900mA 3801 lm 2700K CRI90+ 26° glass incl.driver
 40° ZUMI041960421 Slingshot 3F SLE G7 36,7W 900mA 3801 lm 2700K CRI90+ 40° glass incl.driver

3000K

16° ZUMI041970221 Slingshot 3F SLE G7 36,7W 900mA 4175 lm 3000K CRI90+ 16° glass incl.driver
 26° ZUMI041970321 Slingshot 3F SLE G7 36,7W 900mA 4175 lm 3000K CRI90+ 26° glass incl.driver
 40° ZUMI041970421 Slingshot 3F SLE G7 36,7W 900mA 4175 lm 3000K CRI90+ 40° glass incl.driver

4000K

16° ZUMI041990221 Slingshot 3F SLE G7 36,7W 900mA 4369 lm 4000K CRI90+ 16° glass incl.driver
 26° ZUMI041990321 Slingshot 3F SLE G7 36,7W 900mA 4369 lm 4000K CRI90+ 26° glass incl.driver
 40° ZUMI041990421 Slingshot 3F SLE G7 36,7W 900mA 4369 lm 4000K CRI90+ 40° glass incl.driver

> [DRIVER](#)

Included, if dimmable: DALI.

> [OPTIONS](#)

PC cover

ZUMI01000000500 PC-cover for food environment Ø 111