


PRODUCT DESCRIPTION

Pendant for general or accent lighting.
Aluminium luminaire in several colors and color temperatures with several possible reflectors.

TECHNICAL DATA

Application	Suspension
Dimensions	∅ 800mm h 123mm
IP rating	IP20
Power	230V or 350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
350mA							
2700K	11,8W	13,6W	350mA	1558 lm	134 lm/W	90+	F
	16,9W	19,4W	500mA	2225 lm	134 lm/W	90+	F
3000K	11,8W	13,6W	350mA	1714 lm	147 lm/W	90+	E
	16,9W	19,4W	500mA	2449 lm	147 lm/W	90+	E

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) Tubb: **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
+ (2) Acoustic Disc: **C** (Coffee) / **B** (Tinged with Beige) / **YR** (Tinged with Yellow Red) / **NB** (Night Blue)
+ (3) **G** (gold reflector)

DRIVER INCLUDED - 350mA - non dimmable**2700K**

14°	ZUMI702132306	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 14° glass incl. driver
25°	ZUMI702132406	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 25° glass incl. driver
39°	ZUMI702132506	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 39° glass incl. driver
61°	ZUMI702132606	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 61° glass incl. driver

3000K

14°	ZUMI702142306	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 14° glass incl. driver
25°	ZUMI702142406	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 25° glass incl. driver
39°	ZUMI702142506	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 39° glass incl. driver
61°	ZUMI702142606	Tubb Silenti 800 CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 61° glass incl. driver

DRIVER EXCLUDED - 350mA/500mA**2700K**

14°	ZUMI702132317	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI702132417	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 25° glass excl. driver
39°	ZUMI702132517	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 39° glass excl. driver
61°	ZUMI702132617	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 61° glass excl. driver

3000K

14°	ZUMI702142317	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 14° glass excl. driver
25°	ZUMI702142417	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 25° glass excl. driver
39°	ZUMI702142517	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 39° glass excl. driver
61°	ZUMI702142617	Tubb Silenti 800 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 61° glass excl. driver

> REQUIREMENTS**Round base**ZUMIPD801 (+ W / B) Round base \varnothing 80**3F Adapter***Non dimmable*350mA

white	TRID87500789	Intrack driver LC 25W 350-600mA o4a T EXC3 white
black	TRID87500787	Intrack driver LC 25W 350-600mA o4a T EXC3 black
+	TRID28001110	I-SELECT 2 PLUG 350MA B

500mA

white	TRID87500789	Intrack driver LC 25W 350-600mA o4a T EXC3 white
black	TRID87500787	Intrack driver LC 25W 350-600mA o4a T EXC3 black
+	TRID28001114	I-SELECT 2 PLUG 500MA BL

*Dimmable*350mA

white	TRID87500909	Intrack driver LC 25W 350-600mA o4a T EXC3 white
black	TRID87500908	Intrack driver LC 25W 350-600mA o4a T EXC3 black
+	TRID28001110	I-SELECT 2 PLUG 350MA B

500mA

white	TRID87500909	Intrack driver LC 25W 350-600mA o4a T EXC3 white
black	TRID87500908	Intrack driver LC 25W 350-600mA o4a T EXC3 black
+	TRID28001114	I-SELECT 2 PLUG 500MA BL

> OPTIONS**Honeycomb grid**

ZUMI25HC Honeycomb grid